





- Sub Miniature IEPE Accelerometer
- Shear design
- Piezoelectric ceramic PZT-5
- Sensitivity – 10mV/g
- Mass – 2.6grams
- 6-40 side entry connector
- Adhesive Mount

The SV10S-A is a sub-miniature monoaxial IEPE accelerometer with a side entry 6-40 miniature microdot connector and a flat base for adhesive mounting. Featuring a shear design PZT-5 sensing element the SV10S-A provides high accuracy with wide bandwidth up to 10kHz

Specification	Metric	Imperial
Sensitivity	1.02mV/(m/s ²)	10mV/g
Measurement Range (pk)	±4900m/s ²	±500g
Frequency Range ±10%	1 to 10000 Hz	
Resonant Frequency	≥50 kHz	
Non-Linearity	≤1 %	
Transverse Sensitivity	≤5 %	
Electrical Noise Floor	0.009m/s ² rms	0.0009g rms
Overload Limit (Shock)	±49000(m/s ²)pk	±5000gpk
Operating Temp. Range	-55 to +125°C	-67 to +257°F
Polarity ↑	Positive	
Compliance Voltage (Supply)	+18 to +28 VDC	
Current range	2 – 10mA	
Output Bias Voltage	11VDC ± 1.5VDC	
Size (excluding connector)	8.5mmA/Fx11 mm	Ø0.33" A/Fx0.43"
Weight	2.6gm	0.092oz
Sensing Geometry	Shear	
Sensing Element Material	PZT-5	
Case Material	Titanium	
Connector Position	Side	
Case sealing	Hermetic	
Electrical Connection Type	6-40 Miniature Microdot	
Mounting	Flat base for adhesive mounting	



Kemo has a range of cable assemblies available for use with the SV10S-A and other IEPE accelerometers.

13E2-30 – 3m(10ft) 6-40 microdot to BNC plug
 13E2-50 – 5m(15ft) 6-40 microdot to BNC plug
 13E1-30 – 3m(10ft) 6-40 mdot to 10/32UNFmdot
 13E1-50 – 5m(15ft) 6-40 mdot to 10/32UNFmdot

Kemo Limited

First Floor, 33 King Street, Thetford, Norfolk, IP24 2AW, United Kingdom
 +44 (0)1474 705168

www.kemo.com sales@kemo.com