


- Screened coaxial IEPE sensor cable
- Low outgassing materials for use in Space Applications
- FEP Jacket
- -70°C to +200°C range
- Ideal for IEPE accelerometer sensors
- Black jacket colour
- Nominal diameter 1.9mm
- 10/32UNF Microdot to 10/32UNF Microdot
- Length 3m±5%



Kemo Ltd has been making high quality signal conditioning equipment since 1965 and during this time we have worked with many of the World's largest companies and witnessed many examples of poor-quality instrumentation cables. To resolve this problem Kemo offers its own specialist cable assemblies for the sensor and instrumentation market.

The cables we produce are assembled by Kemo using the highest quality cable and connectors that meet our exacting standards.

For use in vacuum conditions where low outgassing is required, we remove the usual rubber strain relief used on both connectors and replace with a modified fluoropolymer, heat shrink designed for use in space applications. Sometimes referred to as flyaway cables, these low outgassing cables are essential for space applications


Attention is paid to strain relief and correct crimping. Every cable is fully tested and the capacitance checked prior to despatch.

	PTFE	FEP
TML	0.06%	0.01%
CVCM	0.02%	0.00%

**Strain Relief –
NASA Specification SP-R-0022A**
TML 1.0% maximum
CVCM 0.1% maximum

10/32UNF microdot connector	
Physical	Value
Body	Nickel Plated Brass
Knurl nut	Nickel Plated Brass
Centre Conductor	Gold plated brass
Insulator	PTFE
Strain relief boot	Fluoropolymer
Temperature Range	-70°C to +260°C

Cable Electrical Properties	Value
Impedance	50 ±2Ω
Max. Capacitance	100nF/km
Max. Conductor Resistance	355Ω/km
Min. Insulation Resistance	>5000 MΩ/km
Voltage rating	500VAC
Test voltage	3kV DC
Max. Attenuation	108dB/100m
Temp rating	-70°C to +200°C
Min Bending radius	Fixed: 10mm
Min Bending radius	Flexing: 20mm



Layer	Description	Material	Overall diameter
1	Central conductor – multi strand	Silver plated copper clad steel 30AWG (7/0.102mm)	0.30mm
2	Dielectric/Insulation	PTFE	0.86mm ±0.05mm
3	Screen/Outer conductor	Silver Plated Copper Braid Greater than 96% coverage	1.35mm
4	Outer jacket	FEP	1.9mm nom.

Due to continued product development Kemo Limited reserve the right to change specification without notice.

Kemo Limited

First Floor, 33 King Street, Thetford, Norfolk, IP24 2AW, United Kingdom
+44 (0)1474 705168

www.kemo.com sales@kemo.com